

APE-2408G

2.4GHz, 802.11b/g, 800mW/29dBm, Professional

Outdoor AP/client/Repeater/Bridge



3-LED for operation indication and easy diagnosis



Feature Highlights






- on-board 800mW, NO booster (no self harmonic noise), best signal clearness. Up to 25Km
- 8 + 32MB big memory & **automatic watchdog** – no lockups !! **Ideal for WISP**
- Support Multi-SSID and VLAN
- WMM option: Enhance user performance and density QoS
- Highest security level: WPA2/WPA/802.1X
- IP68 water-proof, survive -20C ~ 70C
- 4 programmable operating modes for all aspect applications

AP Specification

Standards Compliance	IEEE 802.11b IEEE 802.11g IEEE 802.3 IEEE 802.3u IEEE 802.3af
SDRAM	32 M Byte
Flash	8 M Byte
Radio Frequency Type	DSSS / OFDM
Modulation	IEEE 802.11b: CCK,DQPSK,DBPSK IEEE 802.11g: OFDM with BPSK, QPSK, 16QAM, 64QAM
Frequency Band	America/FCC: 2.412~2.462 GHz (11 channels) Europe CE/ETSI: 2.412~2.472 GHz (13 channels)
Transmission Power	IEEE 802.11b: 29 dBm@1~11Mbps IEEE 802.11g: 22 dBm@54Mbps; 23dBm@48Mbps; 25dBm@36Mbps; 26dBm@6~24Mbps
Transmission Rate	IEEE 802.11b: 1/ 2/ 5.5/ 11Mbps IEEE 802.11g: 6/ 9/ 12/ 18/ 24/ 36/ 48/ 54Mbps
Access Point Interfaces	Auto MDI/MDI-X Ethernet 10/100Base-TX: RJ-45
Sensitivity	IEEE 802.11b: -98dBm @ 1Mbps; -93dBm @ 11Mbps, PER < 8% IEEE 802.11g: -95dBm @ 6Mbps; -75dBm @ 54Mbps, PER < 10%
Antenna Type	Integrated 15dBi flat panel antenna or external high gain antenna
Security Systems	64-bit/128-bit/152-bit WEP encryption; Wi-Fi Protected Access (WPA)/ WPA2
Wireless Setting	AP/ Client / Wireless Bridge (WDS) PtP and PtMP (up to 16 links)/ Repeater Channel Selection (Setting varies by Country) Adjustable transmit power by 1dBm step
Firmware	Site Survey DHCP Client Suppressed SSID Spanning Tree settings Wireless access control by MAC address filter (up to 50) Multiple SSID with 802.1q VLAN tagging (up to 4 SSIDs) Web-based configuration via popular browser (MS IE, Netscape...) Windows "Locator" program to help find IP in DHCP client mode

	Firmware upgrade and configuration backup via Web Reset to default by WebUI VPN pass-through (PPTP, L2TP, IPSEC) SysLog SNMP v1/v2c MIB support: MIB I, MIB II (RFC-1213) and Private MIB Support QoS(WMM) Support Time settings
Operating Environment	Operating Temperature: -20 ~ +70°C
Power	DC 48 Volt \pm 5%; 0.83A (Max.); AC adapter AC 100V ~ 240V
Regulatory Approval	CE/FCC, RoHS
Network Management System OS Support	Windows 2000/XP, Windows 7
Warranty	One year limited

Standard Accessories

		
25M Cable	2M Cable	PoE (48v, 0.83amp)
		
Bracket Kit (U Bolt)	Bracket Kit	